



VIEW LIVE IMAGES RIGHT BEFORE YOUR EYES

EVEN IN THE BRIGHTEST DAYLIGHT

Optimize your infrared system with *head-up* viewing.

Whether you're an electrical contractor searching for hot spots or a plant engineer performing predictive maintenance on mechanical systems, the CV-3 Video Viewer allows you to focus on both the equipment being inspected and a live video image simultaneously. The viewer provides a floating IR image positioned a few feet in front of you — without obstructing your natural field of vision. Permitting increased mobility and efficiency, you no longer need to divert your attention away to a hand-held monitor. The hands-free, head-up display exhibits unparalleled clarity and outperforms traditional LCD displays. The CV-3 can be viewed outdoors even in the brightest sunlight. Lightweight and comfortable, the viewer easily attaches to prescription or safety eyewear. Why stare at glare? Increase the mobility and efficiency of your workforce today.






 **MicroOptical**





MAKING PORTABLE PRACTICAL.™

www.MicroOptical.net

©2005 The MicroOptical Corporation. "Making portable practical." is a trademark of The MicroOptical Corporation.



APPLICATIONS BENEFITING FROM MOBILE INFORMATION VIEWING



Belt-Worn Battery Dimensions:
3" x 2" x 0.5"

PRODUCT SPECIFICATIONS

CV-3 Video Viewer	
Display Format	640 x 480, 60 Hz refresh rate, landscape
Color Depth	18-Bit (262,144 colors)
Optics Location	Left or right eye configurable
Field of View	Approximately 16° horizontal, 20° diagonal
Focus Range	Adjustable focus from 2 to 15 feet
Input Signal	NTSC/PAL
Input Connector	Male RCA connector, 4'6" cable
Power Requirements	2 W
Power Source	7.2 V lithium ion rechargeable battery
Continuous Operation	5 hours on full charge
Viewer Weight	1.25 ounces (35 grams)
Cable Length	3.5 feet from the viewer to the belt-worn battery
Eyeglass Frame Size	Fits many standard eyeglasses/safety glasses with quick release mount
Operating Temperature	32 to 140°F (0 to 60°C)
Storage Temperature	-4 to 140°F (-20 to 60°C)



Included with the CV-3 color video viewer: mounting kit for use with alternative eyewear, rechargeable lithium ion battery, battery charger, gender changer, optical cloth, user's manual, belt-worn pouch, velour pouch, screwdriver, croakie, UVEX safety eyewear and hard shell carrying case.



www.MicroOptical.net

The MicroOptical Corporation, 33 Southwest Park, Westwood, MA 02090 t: 781.326.8111 f: 781.326.4110

©2005 The MicroOptical Corporation. "Making portable practical" is a trademark of The MicroOptical Corporation. Protected by U.S. Patents 5715377, 5886822, 6023372, 6091546, and other U.S. and International Patents Pending.
MK-0060A 082605 15M